


DIP SWITCH
EP(I)(M) SERIES

End Stackable
Piano Type



FEATURES

- ※Side actuation
- ※End stackable
- ※Through hole or SMT


APPLICATION

- ※Industrial control
- ※Automatic machines control
- ※Telecommunication


SPECIFICATION

Contact Rating	25mA, 24V DC
Contact Resistance	100mΩ max.
Insulation Resistance	100MΩ min. 500V DC
Dielectric Strength	500V AC/1 minute
Operating Force	800gf max.
Travel	20°
Operating Life	2,000 cycles
Operating Temp.	-20°C ~ +85°C
Storage Temp.	-40°C ~ +85°C

HOW TO ORDER



CIRCUIT



PACKAGE




<Tube>

- EP (R)-02: 95 pcs
- EP (R)-04: 47 pcs
- EP (R)-06: 31 pcs
- EP (R)-08: 23 pcs
- EP (R)-10: 18 pcs


<Tape & Reel>

- EPM(R): 700 pcs

EPI(R)



PART NO.	NO.OF POS.	DIM.A	DIM.B
EPI(R)-02	2	4.89	2.54
EPI(R)-04	4	10.06	7.62
EPI(R)-06	6	15.14	12.70
EPI(R)-08	8	20.22	17.78
EPI(R)-10	10	25.30	22.86



P.C.B. LAYOUT

DIP SWITCH


DIP SWITCH
EP(I)(M) SERIES

End Stackable
 Piano Type






EPM(R)

DIP SWITCH




PART NO.	NO.OF POS.	DIM.A	DIM.B
EPM(R)-02	2	4.89	2.54
EPM(R)-04	4	10.06	7.62
EPM(R)-06	6	15.14	12.70
EPM(R)-08	8	20.22	17.78
EPM(R)-10	10	25.30	22.86






P.C.B. LAYOUT

EPI(R)-F



PART NO.	NO.OF POS.	DIM.A	DIM.B
EPI(R)-02F	2	4.89	2.54
EPI(R)-04F	4	10.06	7.62
EPI(R)-06F	6	15.14	12.70
EPI(R)-08F	8	20.22	17.78
EPI(R)-10F	10	25.30	22.86



P.C.B. LAYOUT